




Operating Instructions (EN)


MODELS:


30" Disk 34" Dlisk

29" Cylindrical 33" Cylindrical

> 28" EDGE 32" EDGE









Read these Safety Messages before using the machine.

Scan With Phone for more Information



INTRODUCTION


This manual is furnished with each new machine. This manual will allow the Operator to get the best performance out of your RPS manufactured Scrubber-Drier, Sweeper, Burnisher, or Orbital Scrubber. Read this manual thoroughly before operating or servicing the machine.

This machine will provide excellent performance, but the best results will be obtained at the most minimum costs if:

- The machine is regularly maintained per the Authorized Local Distributor.
- The machine is operated with reasonable care and caution.
- The machine is maintained with manufacturer supplied parts.

LOCATE SERIAL NUMBER

The serial number of your machine is located on the lower half of the control panel of the machine.



AS OUR POLICY IS ONE OF CONSTANT IMPROVEMENT - ALL INFORMATION AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

- 2 - TC-HERO-OP-EN

TABLE OF CONTENTS



Introduction	
Locate Serial Number	2
Table Of Contents	3
⚠ Safety Messages	
Safety Labels	6
LCD Screen	
Operation Controls	
ਛ ⊘ੱ Battery Setup	<u></u>
Remove Squeegee	10
Adjust Squeegee	11
Remove From Battery (Charger12
Transportation - Forwa	rd13
♣ Transportation - Reverse	se14
Fill Solution Tank	15
Deration - Scrubbing	16
🚮 📆 Draining Recovery Tanl	C 17
C Draining Solution Tank	18
Flushing Recovery Tan	k 19
🖍 Clean Drain Saver	20
🚡 Clean Cylindrical Hopp	er 21
Clean Vac Box System	22
Remove Disk Brushes	23
Remove Cylindrical Bru	ushes24
Remove EDGE Pads	25
Charge Batteries	26
Battery Chargers	27
Common Wear Parts	28
	28
	28
-	
Squeegee Blade Kits & 0	Complete Squeegee Assemblies:29



You will see four kinds of safety reminders in this manual:

▲ DANGER

DANGER indicates a hazardous situation which, if not avoided, will result in death or serious injury.

ACAUTION

CAUTION indicates a potentially hazardous situation which, if not avoided, could result in minor or moderate injury or damage to this machine or nearby objects. CAUTION also can be used to alert against unsafe practices.

A WARNING

WARNING indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury.

NOTICE

NOTICE indicates information considered important, but not hazard-related. This safety message may be related to property damage or warranty warnings.

Your safety, and that of others, is very important. Operating this machine safely is an important responsibility.

DO NOT OPERATE THIS MACHINE:

- Unless you are trained and authorized to do so by your RPS Authorized Local Distributor
- Unless you have read and understood this Operator's Manual
- On surfaces with greater than a 2% grade unless this machine is equipped with a functional parking brake
- On surfaces with greater than an 8% grade at any time
- On Loading Docks

WHEN OPERATING THIS MACHINE:

- Remove loose objects from the floor that could be projected from the rotating Brushes
- Keep your hands and feet away from the rotating Brushes
- Do not operate this machine where flammable liquids, vapors, or dust are present
- Use caution when maneuvering

BEFORE LEAVING THE MACHINE:

- Drain "clean" Solution & "dirty" Recovery solution into APPROVED drains
- Park the machine on a level surface
- Turn the machine off & remove key

BEFORE SERVICING THE MACHINE:

Disconnect the Batteries

ADANGER

Explosive hydrogen gas forms when Batteries are charging. An open flame or spark can cause this gas to explode. Serious personal injury or property damage could occur. Only charge the Batteries in this machine in a well ventilated area.

ADANGER

Flammable materials can cause an explosion or fire. Do not use flammable materials in Tank or pick up.

- 4 - TC-HERO-OP-EN

A WARNING

The Batteries in this machine produce hazardous voltage which can cause electrical shock, burns and/ or electrocution. Always disconnect Batteries before servicing this machine.

A WARNING

When climbing or descending ramps, always drive machine forward. To avoid overturning the machine, Do not back down ramps. Do not drive across inclines. Do not turn while ascending or descending ramps. Overturning the machine can cause serious injury or death.

A WARNING

Do not use water that exceeds 135°F / 57°C. If water is above said temperature, this will void the Tank Warranty.

AWARNING

Do not park this machine on ramps or slopes. Always park this machine on a level, hard surface. Do not operate this machine outdoors or on uneven surfaces.

A WARNING

The Batteries in this machine contain sulfuric acid, which causes burns to skin. If battery acid contacts clothing or skin, rinse the effected area with cold water immediately. If battery acid gets on your face or in your eyes, flush the area immediately with cold water and seek medical attention.

▲ WARNING

To avoid electrical shock, do not operate this machine over electrical floor outlets.

ACAUTION

To avoid damage to this machine, use only cleaning solutions and replacement parts recommended by the manufacturer.

▲CAUTION

Do not operate this machine if any parts have been damaged or removed.

A WARNING

Dress safely. Do not wear rings or metal wrist watches when servicing this machine, as they can cause an electrical short circuit which can cause serious burns.

A WARNING

Do not remove, paint over or destroy warning decals. If warning decals become damaged, call 1-262-681-3583 for free replacements.

A WARNING

Dress safely. Do not wear a neck tie, scarf, or any loose or dangling clothing while operating this machine. Loose or dangling clothing or neck-wear can tangle in rotating parts, causing serious injury or death.

A WARNING

Always turn off this machine before leaving it unattended. Do not allow untrained persons to operate this machine.

A WARNING

NO RIDERS. Do not carry passengers on this machine. Do not use this machine as a stepladder or work platform.

A WARNING

Understand the dynamic braking system before you operate the machine on ramps. Machine may coast.

A WARNING

Before you service a Battery, always wear face protection, protective gloves and protective clothing. Battery acid or battery explosion can cause serious injuries.

ACAUTION

Always use the automatic battery charger provided by the manufacturer of this machine to charge the Batteries of this machine. It is designed to charge the Batteries at the appropriate rate. If you must use a different charger, disconnect the Batteries before charging to avoid damage to the electronic speed controller.

ACAUTION

To avoid damage to the electronic control components of this machine, Do not store this machine outdoors. Do not pressure wash this machine.


TC-HERO-OP-EN - 5 -





Read and obey all Safety Labels on your HERO Floor Scrubber. If you have questions about these labels, ask your supervisor.

These images indicate where on the HERO Safety Labels are located. If ever the labels become illegible, worn off, or torn, promptly report it to your supervisor and replace it.





- 6 - TC-HERO-OP-EN




SCREEN #1 (OPERATOR)







SCREEN #3 (WITH ERROR CODE)




** USE GREEN MENU SELECTION BUTTON ON CONTROL PANEL TO CHANGE SCREENS **


- 1. BATTERY LEVEL INDICATOR Indicates the energy level remaining in the Batteries (Shown on all menu displays)
- 2. SOLUTION OUTPUT INDICATOR Indicates the gallons per minute (GPM) 0 1.0
- 3. SCRUBDECK DOWN PRESSURE INDICATOR Sets the down pressure on the Brushes / Pads
- 4. SCRUB MOTORS ON Indicates the Brush Motors are in operation
- 5. SOLUTION ON Indicates the solution flow is ON
- **6. VACUUM ON Indicates the Vacuum is** *ON*
- 7. KEY SWITCH HOUR METER Indicates total hours the machine has had keyswitch ON
- 8. TRANSPORT HOUR METER Indicates total hours the drive system has been in operation
- 9. SCRUB BRUSH HOUR METER Indicates total hours the brush motors have been in operation
- 10. VACUUM HOUR METER Indicates total hours the vacuum motor has been used
- 11. DIAGNOSTIC CODE Displays diagnostic code which helps troubleshoot issues
- 12. ERROR WARNING SYMBOL Indicates when there has been a diagnostic code error


TC-HERO-OP-EN - 7 -















- 8 - TC-HERO-OP-EN











24 VOLTS

NOTICE


Batteries are a possible environmental hazard. Consult your Battery supplier for safe disposal methods.


NOTICE


Orientation of Batteries is critical for cables to reach. Ensure proper torque values when installing batteries. (Between 8 - 12 ft/lbs)


TC-HERO-OP-EN - 9 -













- 10 - TC-HERO-OP-EN


ADJUST SQUEEGEE






TC-HERO-OP-EN - 11 -








Please refer to OEM Charger Operating Instructions for more information.



TRANSPORTATION - FORWARD






TC-HERO-OP-EN - 13 -









- 14 - TC-HERO-OP-EN





ADANGER

EXPLOSION RISK! Flammable materials can cause an explosion or fire. Do NOT use flammable materials in Tank or pick up.




ACAUTION


TO AVOID DAMAGE TO THIS MACHINE:


- Use APPROVED detergents only
- Water temperature must not exceed 130°F/54°C
- Do NOT use high-percentage Bleach mixture



TC-HERO-OP-EN - 15 -









- 16 - TC-HERO-OP-EN

DRAINING RECOVERY TANK











TC-HERO-OP-EN - 17 -










- 18 - TC-HERO-OP-EN

FLUSHING RECOVERY TANK











TC-HERO-OP-EN - 19 -











CLEAN CYLINDRICAL HOPPER










TC-HERO-OP-EN - 21 -





















REMOVE DISK BRUSHES










TC-HERO-OP-EN - 23 -











- 24 - TC-HERO-OP-EN


REMOVE EDGE PADS









TC-HERO-OP-EN - 25 -






Please refer to OEM Charger Operating Instructions for more information.



- 26 -TC-HERO-OP-EN

BATTERY CHARGERS



Console / WET / Domestic Chargers:






AC Power IN: 120VAC / 60Hz DC Power OUT: 24VDC / 30A

Please refer to OEM Charger Operating Instructions for more information.



Onboard / AGM / International Chargers:





AC Power: 80-270VAC / 50-60Hz **DC Power OUT:** 24VDC / 27A

Please refer to OEM Charger Operating Instructions for more information.



TC-HERO-OP-EN - 27 -

COMMON WEAR PARTS

ROUND DISK BRUSHES:

NOTICE

The ## in Disk Column Denotes Desk Pad Size: 15" or 17"

BRUSHES	DISK	LEVEL
Super Grit	##-382SS	Very High
Tough Grit	##-382S	High
Midi Grit	##-382C	Medium
Light Grit	##-382PS	Moderate
Poly	##-382P	Light
Nylon	##-382N	Light
Tampico	##-382T	Light
Pad Driver	##-382D	
Diamond Driver	##-382DD	

ROUND DISK PADS:

NOTICE

The ## in Disk Column Denotes Desk Pad Size: 15" or 17" $\,$

DISK PADS	DISK	LEVEL	COLOR
Super Black	##-422BB	Very High	Black
Black	##-422B	High	Black
Brown	##-422BR	High	Brown
Green	##-422G	Medium	Green
Blue	##-422BL	Moderate	Blue
Red	##-422R	Moderate	Red
White	##-422W	Light	White

CYLINDRICAL BRUSHES:

BRUSHES	MODEL 29" CYLINDRICAL	MODEL 33" CYLINDRICAL	LEVEL
Tough Grit	276-697S	316-697S	High
Midi Grit	276-697C	316-697C	Medium
Light Grit	276-697PS	316-697PS	Moderate
Nylon	276-697N	316-697N	Light
Tampico	276-697T	316-697T	Light

EDGE PADS AND SCREENS:

DESCRIPTION	28"×14" SCRUBDECK	32"×14" SCRUBDECK
White Pad	EDGE-4054	EDGE-5005
Red Pad	EDGE-4053	EDGE-5004
Blue Pad	EDGE-4052	EDGE-5009
Green Pad	EDGE-4051	EDGE-5002
Black Pad	EDGE-4050	EDGE-5001
White Driver Pad	EDGE-4058	N / A
60 Grit Sand Screen	EDGE-4059	N/A
80 Grit Sand Screen	EDGE-4060	N/A
100 Grit Sand Screen	EDGE-4061	EDGE-5028
120 Grit Sand Screen	EDGE-4062	EDGE-5029
150 Grit Sand Screen	EDGE-4063	N/A
Tile/Grout Renovator Pad	EDGE-4048	N/A
Dominator HD Strip Pad	EDGE-4055	N/A
Maroon ECO Prep Pad	EDGE-4056	EDGE-5007
Remover Burnishing Pad	EDGE-4057	EDGE-5008
Porko Burnishing Pad	EDGE-4047	N/A
Velcro Pad	300-4024	N/A

- 28 - TC-HERO-OP-EN

EDGE GRIP FACE:

DESCRIPTION	PART#
28" Velcro Grip Face	300-1039
28" Mighty Lok Grip Face	300-01037Z
32" Mighty Lok Grip Face	300-01037Z

SQUEEGEE BLADE KITS & COMPLETE SQUEEGEE ASSEMBLIES:

SQUEEGEE SIZE	30" DISK DECKS	34" DISK DECKS	29" CYL. DECKS	33" CYL. DECKS	28" EDGE DECKS	32" EDGE DECKS
36" Squeegee	Standard	Optional	Standard	Optional	Standard	Optional
42" Squeegee	Optional	Standard	Optional	Standard	Optional	Standard

SQUEEGEE SIZE	LINATEX BLADE KIT	GUM RUBBER BLADE KIT	URETHANE BLADE KIT	COMPLETE SQUEEGEE ASSEMBLIES
36" Squeegee	36-770L	36-770G	36-770U	36-7180
42" Squeegee	42-770L	42-770G	42-770U	42-7180


SQUEEGEE MATERIAL:	USED FOR:
LINATEX	Provides best wear and tear resistance. Not designed for use with harsh chemicals.
URETHANE	Provides best resistance when dealing with harsh chemicals, oils, fuels, etc.
GUM	Provides best drying preformance on rough/grouted floor types by sealing over irregularities. Short life.

NOTICE

Squeegee blade kits include (1) Rear Blade, (1) Front Blade, and (2) Caster Wheels with hardware.

NOTICE

Squeegee Assemblies (complete) listed above all come with Linatex blades.



TC-HERO-OP-EN - 29 -







1711 South Street Racine, WI 53404 www.tomcatequip.com Tel. US: 800-450-9824

Tel. Int: (+001) 262-681-6470